

teXXmo *your ticket to mobility!*

KALEO DT395CR



teXXmo

Mobile Solution
GmbH & Co. KG
Otto-Lilienthal-Str. 36
D-71034 Böblingen

fon +49 70 31-71 48 50
fax +49 70 31-71 48 49

www.teXXmo.com
info@teXXmo.com

KALEO DT395CR

System - System	
CPU <i>Prozessor</i>	Intel® Atom™ Quad Core, 1.44GHz (up to 1.84GHz)
RAM <i>Arbeitsspeicher</i>	4GB
Storage <i>Festplattenkapazität</i>	64GB to 128GB
Operating System <i>Betriebssystem</i>	Microsoft® Windows® 10 IoT Enterprise, Android 5.1
Display <i>Bildschirm</i>	22.6 cm (8,9") LED-backlight, capacitive touch, anti-reflection outdoor viewable
Display Resolution <i>Bildschirmauflösung</i>	1920 x 1200 (WUXGA)
Network <i>Netzwerk</i>	Wi-Fi 802.11ac; 2.4GHz/ 5GHz dual band; Bluetooth 4.0 LE
Control Switch and Button <i>Tasten</i>	1 power button, 1 trigger button, 1 brightness control button and 1 up/down button
Indicator <i>Anzeigen</i>	1 display mode LED and 1 battery status LED
Speaker and Microphone <i>Lautsprecher und Mikrofon</i>	Built-in speaker and microphone
SD Slot <i>SD-Kartenleser</i>	1 micro-SD card slot
I/O Ports - Anschlüsse	
USB 2.0 Port <i>USB 2.0 Anschluss</i>	1
Audio Jack <i>Audio-Buchse</i>	1
Power-in <i>Stromanschluß</i>	1
Mechanical and Environmental - Umgebung	
AC/DC Adapter <i>Netzteil</i>	Input: 100 – 240V AC; Output: 19V DC, 3.42A
Battery Pack <i>Akkupack</i>	Internal 3.6V, 8800mAh
Enclosure <i>Gehäuse</i>	ABS + PC plastics
Stylus <i>Stift</i>	Yes, capacitive touch stylus
Protective Grips <i>Schutzecken</i>	Rubber bumpers on each corner for handling protection
Dimensions (H x W x D) <i>Abmessungen (H x B x T)</i>	196 x 256 x 33.5 mm
Weight <i>Gewicht</i>	1.3 kg
Water and Dust Resistance <i>Schutz gegen Nässe u. Staub</i>	IP65
Shock and Vibration <i>Schock und Vibration</i>	MIL-STD-810G
Regulatory <i>Zertifizierungen</i>	CE, FCC Class B, RoHS compliant
Temperature <i>Temperatur</i>	Operation: -10°C to +40°C; Storage: -20°C to 60°C
Humidity <i>Luftfeuchtigkeit</i>	0% – 90% non-condensing
Options - Optionen	
Camera <i>Kamera</i>	5 megapixel front and back cameras
Barcode Scanner (2D) <i>Barcode Scanner (2D)</i>	2D barcode scanner; reads 1D also
I/O Ports <i>Anschlüsse</i>	EIA/RS-232/422/485 and Ethernet ports, 6-pin lockable connector included
Mobile broadband <i>Mobiles Breitband</i>	4G LTE/AWS



Desktop Cradle



Wall/Vehicle Cradle




Power Bank



Battery Charger



Serial Cable



Shoulder Strap



Stylus



DC/DC-Adapter



Protective Foils

teXXmo

Mobile Solution
GmbH & Co. KG
Otto-Lilienthal-Str. 36
D-71034 Böblingen

fon +49 70 31-71 48 50
fax +49 70 31-71 48 49

www.teXXmo.com
info@teXXmo.com